

# EA900G4

6 kVA ~ 20 kVA (3:1)

PF 1.0

## APPLICATION: COMPUTER APPLICATION



### Features

- Advanced DSP (Digital signal processors) technology
- Variable speed fan
- Effective software and hardware protection function, robust self-diagnostic function, and abundant event log for check
- Advanced digital parallel technology
- Wide input voltage range, 50 / 60 Hz frequency auto sensing
- Linear derating in low voltage input reducing battery discharging times, extending the service life of battery
- Dual-input design, supporting independent bypass
- Output power factor improved from 0.9 to 1, load capacity increased by 13%
- Flexible battery configuration (settable 16 - 20 pcs batteries)
- Charging voltage and current configured by demands
- Ability to switch on the UPS with batteries
- Settable delayed start time when mains power is restored, reducing the impact on power grid or generator
- Two modes of frequency conversion: 50 Hz input / 60 Hz output or 60 Hz input / 50 Hz output

- LCD+LED display, multi-functional keys operation, friendly human-machine interface
- Powerful background software for parameters configuration
- Compact internal layout, miniaturized the complete unit for small footprint
- Advanced multi-platform communications: RS232, USB, RS485, SNMP and dry contacts communication interfaces
- Intelligent battery management, automatic floating / equalizing charge control, charger dormancy control, increasing battery life by 50%
- Active power factor correction (APFC), input power factor up to 0.99
- High efficiency 95% (up to 98% in ECO mode)
- Equipped with self-aging function

### Available Options

- RS232 and smart card slot included
- Optional parallel function, battery temperature compensation, SNMP card, USB, RS485 card, dry contacts, EMD, and SMS alarms

### Rear Panel

1. RS232
2. EPO
3. Parallel port (optional)
4. USB (optional)
5. Temperature detection (optional)
6. SNMP (optional)
7. Reserved: for customer function such as manual bypass, battery breaker, socket ect.
8. Fans
9. Bypass breaker
10. Input breaker
11. GND
12. Terminals and terminal cover



6 kH / 10 kH

15 kH / 20 kH

6 kS / 10 kS

### Specifications

MODEL	6 kVA	12 kVA	15 kVA	20 kVA
Capacity	6 kVA / 6000 W	12 kVA / 12000 W	15 kVA / 15000 W	20 kVA / 20000 W
<b>INPUT</b>				
Input wiring	Three-phase five-wire (3Φ + N + PE)			
Rated voltage	380 V / 400 V / 415 Vac			
Voltage range	190 ~ 305 Vac (linear derating between 50% and 100% load); 305 ~ 499 Vac (no derating)			
Rated frequency	50 / 60 Hz (auto-sensing)			
Frequency range	40 ~ 70 Hz			
Power factor	≥ 0.99			
Bypass voltage range	- 40% ~ +15% (settable)			
Total harmonic distortion (THDI)	≤ 5%			
<b>OUTPUT</b>				
Output wiring	Single-phase three-wire (1Φ + N + PE)			
Rated voltage	208 V (PF=0.9) / 220 V / 230 V / 240 Vac			
Voltage regulation	± 1%			
Frequency	Synchronized to bypass in mains mode; 50 / 60 Hz ± 0.1% Hz in battery mode			
Waveform	Sinusoidal			
Power factor	1			
Total harmonic distortion (THDV)	≤ 1% (linear load); ≤ 3% (non-linear load)			
Crest factor	3:1			
Overload capability	102% ~ 110% for 10 min, 110% ~ 125% for 1 min, 125% ~ 150% for 30 s			
<b>BATTERIES</b>				
DC voltage	192 Vdc (192 / 240 Vdc settable)			
Number of battery	16 pcs (16 ~ 20 settable)			
Inbuilt battery (standard model)	12 / 7 Ah x 16	12 / 9 Ah x 16	/	/
Charging current	Standard model: 1 A; Long time model: 5 A (default), 1 ~ 5 A settable; 10 A (optional)			
Recharge time	Standard model: 90% capacity restored in 8 hours; Long time model: depend on the capacity of battery			
<b>SYSTEM</b>				
Efficiency	≥ 94% at 100% load, max. 95% at 60% load, ≥ 98% in ECO mode			
Switching time	0 ms			
Protections	Short-circuit, overload, overtemperature, battery low voltage, overvoltage, undervoltage and fan failure			
Max. number of parallel connections	4			
Communications	RS232 (standard), USB / RS485 / dry contacts / SNMP / battery temperature compensation (optional)			
Display	LCD + LED			
<b>OTHERS</b>				
Operating temperature	0°C ~ 40°C			
Storage temperature	-25°C ~ 55°C (without battery)			
Humidity	0 ~ 95% (non-condensing)			
Altitude	≤ 1000 m, derating 1% for each additional 100 m			
IP rating	IP 20			
Noise level at 1 m	≤ 58 dB			
Dimensions (W x D x H) (mm)	191 x 496 x 711 (S) 191 x 496 x 350 (H)		191 x 495 x 515 (H)	
Packaged dimensions (W x D x H) (mm)	685 x 310 x 941 (S) 617 x 318 x 475 (H)		593 x 285 x 618 (H)	
Net weight (kg)	58.5 (S) 18.5 (H)	64 (S) 18.5 (H)	26.5 (H)	
Gross weight (kg)	66.5 (S) 20 (H)	72 (S) 20 (H)	28 (H)	

\* S means standard model; H means long time model.  
\* All specifications are subject to change without notice.

**EAST GROUP CO. LTD**